

Safety Data Sheet



Issue Date 01-Aug-2013

Revision Date: 01-Aug-2015

Version 1

1. IDENTIFICATION

Product Identifier

Product Name Weaver Pro Touch Rust

Other means of identification

SDS # 69-2103

UN/ID No UN1950

Product Code 69-0610

Other Information Formula: 55072.

Recommended use of the chemical and restrictions on use

Recommended Use Cover stains and blemishes.

Details of the supplier of the safety data sheet

Supplier Address

WEAVER LEATHER LLC

7540 CR 201

MT HOPE OH 44660

www.weaverleather.com

Emergency Telephone Number

Company Phone Number 330-674-7548 – PHONE

330-674-6859 – FAX

Emergency Telephone (24 hr) CHEMTEL 1-800-255-3924

2. HAZARDS IDENTIFICATION

Appearance Aerosols

Physical State Aerosol

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Aerosols	Category 1

Hazards Not Otherwise Classified (HNOC)

May be harmful in contact with skin

Signal Word

Danger

Hazard Statements

Causes skin irritation

Causes serious eye irritation

May cause genetic defects

May cause cancer

Suspected of damaging fertility or the unborn child

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Extremely flammable aerosol

**Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash it before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do not induce vomiting

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Toxic to aquatic life with long lasting effects

Unknown Acute Toxicity

4.7% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Hexane	110-54-3	57-63
Petroleum gases, liquified, sweetened	68476-86-8	27-33
Yellow Iron Oxide	51274-00-1	1-5
Propylene glycol monomethyl ether acetate	108-65-6	1-5
Iron(III) oxide	1309-37-1	1-5

4. FIRST-AID MEASURES

First Aid Measures

General Advice	If exposed or concerned: Get medical advice/attention.
Eye Contact	If adverse effects occur, rinse eyes with large amounts of water until irritation subsides. If eye irritation persists: Get medical advice/attention.
Skin Contact	Wash with soap and water. Apply hand cream. Get medical attention if irritation occurs. Take off contaminated clothing. Wash contaminated clothing before reuse.
Inhalation	Remove to fresh air.
Ingestion	Do not induce vomiting. Call a physician or poison control center immediately.

Most important symptoms and effects

Symptoms	Aspiration hazard: if swallowed can enter lungs and cause damage. Overexposure by inhalation can cause headaches, nausea, dizziness, decreased blood pressure. Can cause defatting of skin tissue. Prolonged contact may cause painful stinging or burning of eyes and lids, watering of eye, and irritation.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Aerosol flame projection test: >18" extension at 70 F. Aerosols are under pressure. Aerosols may rupture violently at temperatures above 120 F. Vapors may form explosive mixtures with air.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Use personal protective equipment as required. Remove all sources of ignition.

Environmental Precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protection recommended in Section 8. Wash thoroughly after handling. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Do not spray near open flame. Pressurized container: Do not pierce or burn, even after use. Do not drop. Avoid over-spraying onto floors-slippery surface may result.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from direct sunlight. Do not store at temperatures above 120°F. Do not handle or store near any sources of ignition. Store locked up.

Incompatible Materials Oxidizers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Hexane 110-54-3	TWA: 50 ppm S*	TWA: 500 ppm TWA: 1800 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 180 mg/m ³	IDLH: 1100 ppm TWA: 50 ppm TWA: 180 mg/m ³
Iron(III) oxide 1309-37-1	TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ fume TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ fume and total dust (vacated) TWA: 5 mg/m ³ respirable fraction regulated under Rouge	IDLH: 2500 mg/m ³ Fe dust and fume TWA: 5 mg/m ³ Fe dust and fume

Appropriate engineering controls

Engineering Controls Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Proper eye care is needed in all industrial operations.

Skin and Body Protection Protective gloves are not required, but recommended.

Respiratory Protection Ensure adequate ventilation, especially in confined areas.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Aerosol	Odor	Not determined
Appearance	Aerosols	Odor Threshold	Not determined
Color	Medium brown		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not determined	
Melting Point/Freezing Point	< -40 °C / <-40 °F	
Boiling Point/Boiling Range	39-40 °C / 103-104 °F	
Flash Point	Not determined	
Evaporation Rate	Fast	
Flammability (Solid, Gas)	Flammable aerosol	
Upper Flammability Limits	7.5%	
Lower Flammability Limit	1.2%	
Vapor Pressure	137 mm Hg	@ 21°C (70°F)
Vapor Density	>1	(Air=1)
Specific Gravity	0.644	(1=Water)
Water Solubility	Nil	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Autoignition Temperature	Not determined	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	
VOC Content (%)	96%	
Density	5.378 weight/gal	

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Avoid temperatures above 120°F. Avoid direct sunlight.

Incompatible Materials

Oxidizers.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact	Causes serious eye irritation.
Skin Contact	Causes skin irritation. May be harmful in contact with skin.
Inhalation	Avoid breathing vapors or mists.
Ingestion	Do not taste or swallow.

Component Information

<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Inhalation LC50</u>
Hexane 110-54-3	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h
Propylene glycol monomethyl ether acetate 108-65-6	= 8532 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	-
Iron(III) oxide 1309-37-1	> 10000 mg/kg (Rat)	-	-

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity Isobutane is considered a carcinogen when it contains \geq 0.1% of 1,3-butadiene.

Chemical Name	ACGIH	IARC	NTP	OSHA
Iron(III) oxide 1309-37-1		Group 3		

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity Suspected of damaging fertility or the unborn child.

STOT - single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity

Not determined

Unknown Acute Toxicity 4.7% of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Hexane 110-54-3		2.1 - 2.98: 96 h Pimephales promelas mg/L LC50 flow-through		1000: 24 h Daphnia magna mg/L EC50
Propylene glycol monomethyl ether acetate 108-65-6		161: 96 h Pimephales promelas mg/L LC50 static		500: 48 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined

Bioaccumulation

Not determined

Mobility

Chemical Name	Partition Coefficient
Petroleum gases, liquified, sweetened 68476-86-8	2.8
Propylene glycol monomethyl ether acetate 108-65-6	0.43

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated Packaging	Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Hexane 110-54-3	Toxic Ignitable

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2.1

IATA

UN/ID No	UN1950
Proper Shipping Name	Aerosols, flammable
Hazard Class	2.1

IMDG

UN/ID No	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2.1
Marine Pollutant	This material may meet the definition of a marine pollutant

15. REGULATORY INFORMATION

International Inventories

TSCA Listed

Legend:

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory*
- DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List*
- EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances*
- ENCS - Japan Existing and New Chemical Substances*
- IECSC - China Inventory of Existing Chemical Substances*
- KECL - Korean Existing and Evaluated Chemical Substances*
- PICCS - Philippines Inventory of Chemicals and Chemical Substances*

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Hexane 110-54-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

SARA 313

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Hexane - 110-54-3	110-54-3	57-63	1.0

US State Regulations**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Hexane 110-54-3	X	X	X
Iron(III) oxide 1309-37-1	X	X	X

16. OTHER INFORMATION**NEPA****Health Hazards****Flammability****Instability****Special Hazards** Not

Not determined

Not determined

Not determined

determined **Personal****HMIS****Health Hazards****Flammability****Physical Hazards****Protection B**

2

4

0

Issue Date

01-Aug-2013

Revision Date:

01-Aug-2015

Revision Note

New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet